

# RGBlink vue PTZ camera



Front View



Rear View



Left View

## Key Features

- High speed optical zoom
- RTSP/RTMP/SRT encoding output
- High performance in low light scenarios with wide dynamic range
- Full 1920×1080p HD resolutions up to 60 frames per second
- H.265/H.264 dual stream output adapted to different network environments
- Pan and Tilt control

- 12X/20X/30X optical zoom
- NDI | HX output for PNDI model camera
- Applicable to meeting, live streaming, church, classroom and more
- Low-power Sleep Function
- Support TALLY
- Support PoE

## Specification

Interface	Output	3G SDI HDMI USB LAN	1xBNC 1xHDMI-A 1xUSB-A 1xRJ45	
	Audio	IN	1x3.5mm Stereo Jack	
	Control	RS232 IN/OUT RS485	2xDIN8 1x4pin Terminal	
	Power		1xDC12V Jack	
Performance	Camera		12X                      20X                      30X f=4.1~49.2mm          f=4.8~96mm          f=5.2~148.4mm View Angle              6.57°~ 70.28°          3.45°~ 60.04°          2.14°~58.1° AV                          F1.8 ~ F2.68              F1.8 ~ F2.9              F1.3 ~ F4.8 Digital Zoom              10X Minimum Illumination    0.5Lux (F1.8, AGC ON) DNR                          2D & 3D DNR White Balance              Auto/Manual/One Push/3000K to 7000K(selectable) Focus                          Auto/Manual Aperture/Electronic Shutter    Auto/Manual BLC                            ON/OFF WDR                           OFF/Dynamic Level Adjustment Video Adjustment            Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve SNR                           >55dB Effective Pixels              2.07 megapixels Sensor                        1/2.8 inch HD CMOS Sensor	
	Pan-and-Tilt Parameter	Pan/Tilt Movement Pan/Tilt Control Speed Preset Speed/Quantity 360° TALLY	-170°~+170°/-30°~+90° 0.1~60°/S; 0.1~30°/S Pan:60°/S, Tilt:30°/S; Up to 255 preset positions (10 remote control) full 360° view of TALLY	
	Audio Compression Format	AAC   MP3   G.711A		
	Video Compression Format	H.264   H.265   Dual Streaming Output		
	Output Resolutions	1080p60/59.94/50/30/29.97/25   1080i60/59.94/50   720p60/59.94/50		
	Control Protocol	VISCA   Pelco-D   Pelco-P   ONVIF		
	Baud Rate(bps)	115200   9600   4800   2400bps		
	Network Protocol	RTSP   RTMP   ONVIF		
	Supported Standards	SDI                          SMPTE 425M (Level A & B)   SMPTE 424M   SMPTE 292M   SMPTE 259M-C   DVB-ASI		
	Power	Input Voltage	DC12V/1.5A	
		Max Power	12W	
	Environment	Temperature	-10℃~50℃	
		Humidity	20%~80%	
	Physical	Weight	Net	1.7kg
	Dimension	Net	180mm(front)×188mm(side)×198mm(height)	

## Order Codes

Product Code	Item
981-0011-27-0	RGB20X-PoE-TLY, 20X PTZ Camera with TALLY (Support PoE)
981-0011-28-0	RGB20X-PNDI-TLY, 20X NDI Camera with TALLY (Support PoE)
981-0011-29-0	RGB20X-USB-TLY, 20X USB PTZ Camera with TALLY
981-0011-31-0	RGB12X-PoE-TLY, 12X PTZ Camera with TALLY (Support PoE)
981-0011-32-0	RGB12X-PNDI-TLY, 12X NDI Camera with TALLY (Support PoE)
981-0011-33-0	RGB30X-PoE-TLY, 30X PTZ Camera with TALLY (Support PoE)
981-0011-34-0	RGB30X-PNDI-TLY, 30X NDI Camera with TALLY (Support PoE)

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.

**RGBlink**  
www.rgbink.com

